



ABYSS® Online BioGas Analysers

Description - The ABYSS BioGas NDIR gas analyser series is specially designed for continuous and simultaneous monitoring of primary biogas constituents CH₄, CO₂, O₂ and H₂S. The ABYSS BioGas fulfils the requirements of waste recycling facilities and associated odour filtration systems. It is based on the micro-flow type non-dispersive infrared (NDIR) method for CH₄ and CO₂, and uses a Thermal Conductivity Detector (TCD) for H₂S and O₂.

Applications - Standards applications are wastewater treatment plant, odour control system, landfill, anaerobic digestion and other fermentation processes.

Highly durable to harsh process conditions - The ABYSS BioGas 19"inch rack mount enclosure fitted with LCD screen, safety filter and built-in flowmeter enables efficient long term measurement of up to 4 gases in emissions and process gas. An automatic built-in gas diluter reduce instruments recovery time in case of high and unstable gas concentrations. The ABYSS analysers are built, calibrated and factory tested in Belgium and certified C.E. by Ankersmid Sampling BVBA.

ABYSS® ABG

High Performance Online
Monitoring



CO₂

CH₄

H₂S

O₂



ANKERSMID
Sampling

ABYSS® Key Features

- Proprietary infrared single beam Micro-Flow NDIR detectors
- Cross interference compensation
- RS 232 serial com port for real-time data download to external PC or laptop as text file,
- Cost-effective BioGas online monitoring solutions
- Fully automatic standalone system for fast, accurate and reliable analysis of primary biogas constituents
- Keyboard / LCD display interface for configuration & calibration
- Online monitoring of 4 gases simultaneously
- 19 inch rack mount enclosure
- Stainless steel connectors for gas inlet/outlet and zero air inlet ports, Built-in Sampling Pump and flowmeter
- Dual CEMS (2 streams simultaneously) and multiplexed (up to 4 streams) systems empowering cost efficient multipoint monitoring
- PFA and PTFE gas path



BioGas Stationary Monitoring System

When sampling gas from landfill, anaerobic digestion/bacteria and other fermentation processes, the use of a dedicated sampling system is necessary to ensure application specific sample preparation and to preserve your monitoring equipment. AquaGas Sampling solutions cover a large range of applications and enable efficient BioGas online measurement with automated sampling sequences, multipoint monitoring, high performance gas conditioning and deep filtration features.



ABYSS® Specifications

	INTEGRATION	GAS	MODELS	APPLICATIONS
Dimensions	19inch rack mount unit	CH4 - CO2 - H2S - O2	ABG700	BioGas
Weight	432x420x132mm wxhxd 12kg	CH4 - CO2 - H2S	ABG600	BioGas
Flow	0.7 to 1.2 lpm	CH4 - CO2 - O2	ABG500	BioGas
Response time	TD+T90 < 15s (NDIR)	CH4 - CO2	ABG400	BioGas
Warm- up time	5 min	CH4 - H2S	ABG300	BioGas
inlet pressure	2kPa - 50kPa	CH4 - O2	ABG200	BioGas
Interface	LCD display + keyboard	CH4	ABG100	BioGas
Output	RS232 / 4-20mA / dry contact alarm			
Power supply	240 VAC 50 +/-1Hz			
Operating conditions	Temp 0-50C Pressure 86-108kPa Humidity 5-85% non-condensing			

GAS	TECHNOLOGY	RANGE (max/min)	PRECISION	RESOLUTION	REPEATABILITY
CO2	NDIR	0 - 50 %	≤±2% FS	0.1 %	≤±2% FS
CH4	NDIR	0 - 100 %	≤±2% FS	0.1 %	≤±2% FS
H2S	TCD	0 - 10 000 PPM	≤±3% FS	1 PPM	≤±2% FS
O2	TCD	0 - 25 %	≤±3% FS	0.1 %	≤±2% FS

